

PRODUCT DATASHEET LED PFM BULKHEAD CIRCULAR 21W 4000K

LED PERFORMANCE ALUMINIUM BULKHEAD | Aluminium bulk head family with high IP rating



Areas of application

- Workshops, garages, covered outdoor storage areas
- Gardens, balconies and other outdoor areas

Product benefits

- Compact and robust design
- Motion sensor version available
- Stylish and modern design

Product features

- Die-cast aluminum housing with PC front cover

Impact resistance: IK07Type of protection: IP54



TECHNICAL DATA

Electrical data

Nominal wattage	21.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	95.000 mA
Protection class	1

Photometrical data

Luminous flux	1700 lm
Luminous efficacy	81 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80

Dimensions & Weight

Diameter	275.00 mm
Height	75.00 mm
Product weight	1120.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Plastic
Mercury content	0.0 mg

Application & Mounting

Type of connection	Terminal
Type of protection	IP54
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
LED module replaceable	Not replaceable

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction
	Tender documents
<u></u>	IES file (IES)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075388086	Folding box 1	283 mm x 83 mm x 283 mm	1364.00 g	6.65 dm ³
4058075388093	Shipping box 8	592 mm x 347 mm x 307 mm	11609.00 g	63.07 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.