## Catalogue No: CA9-305-11-120W-KIT

## KIT CONTACTOR 160kW 3P 100-250V AC/DC COIL 1NO 1NC AUX

Motor Control and Drives > Motor Starting and Protection > Contactors > Sprecher + Schuh Contactors > CA9 Contactors 55 to 630kW > 3 Pole Contactors with AC/DC Coil



- Simplifies selection with electronic wide-range AC/DC coils
- Available integrated PLC interface
- Saves energy with low power consumption
- Includes built-in surge suppression
- For ease of change over, adaptor plates available in KIT form for CA6 to CA9 migration

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	CA9
Component Type Motor Control and Drives	Standard Contactor
le, Rated Operational Current, AC-1, 690V, 40°C	500 A@690V,40°C
le, Rated Operational Current, AC-1, 1kV, 40°C	375 A@1kV,40°C
kW Rating, AC-3, 415V, 60°C	160 kW @415V, 60°C
le, Rated Operational Current, AC-3, 415V, 60°C	305 A@415V,60°C
kW Rating, AC-3, 690V, 60°C	250 kW @690V, 60°C
le, Rated Operational Current, AC-3, 690V, 60°C	290 A@690V,60°C
kW Rating, AC-3, 1kV, 60°C	132 kW @1kV, 60°C
le, Rated Operational Current, AC-3, 1000V, 60°C	100 A@1000V,60°C
Coil Туре	Electronic type
REFERENCES	
IECEx Certificate -	
Supplier Declaration of	
Conformity:	
Installation Guide: -	
User Manual: -	
Manufacturer Datasheet: -	
Manufacturer Catalogue & Product Selection:	

