

Catalogue No: 1794-IRT8XT

FLEX I/O XT 8AI THERMOCOUPLE/RTD/MV MODULE

Automation Systems > Distributed I/O and Signal Converters > Fieldbus I/O Systems > Allen-Bradley FLEX™ I/O > Allen-Bradley FLEX™ I/O (1794, 1797) > FLEX-I/O XT™ Extreme Environment Specialty Modules



FLEX I/O-XT, Input Module, Non-Isolated, Thermocouple/RTD/Mv

- Extreme environment modules operate in a broader temperature range (-20C to 70C)



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	Flex I/O XT (Bul. 1794)
Component Type Fieldbus I/O	I/O - Specialty Module
Power Supply	24V DC
Operating Temperature, Max	70 °C max
Operating Temperature, Min	-20 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-