## Catalogue No: **D7-AF1CE110**

## COLOUR CAP FOR FLUSH NON-ILLUM PUSHBUTTON WHITE DOWN

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Sprecher + Schuh D7 Pushbuttons and Pilot Lights > D7 Accesories > Colour Caps for Non-Illuminated Pushbuttons





Colour cap White flush "DOWN"

- The D7 range of 22.5mm operator control devices includes a diverse range of products making it suitable for use in a wide range of applications. Products in the range include pushbuttons, selector switches, pilot lights, emergency stop operators and more.
- Aesthetically appealing and modularly designed to make assembly and interchangeability easy.
- Operators exhibit low profile and stylish appearance while maintaining the rugged performance necessary for demanding environments
- Operators are available in both plastic (D7P) and metal (D7M) variants.

Representative Photo Only (actual product may vary based on configuration selections)

| SPECIFICATIONS                             |  |
|--|--|
| Product Series                             | D7 22.5mm Control & Indication   |
| Component Type Pushbutton and Pilot Lights | Colour Cap / Diffuser  |
| Details, compatible Product Series         | Suits Flush, non-illuminated pushbutton.   |
| Colour                                     | White  |
| Colour, Text                               | Black colour   |
| Text, Operator                             | DOWN   |
| RoHS Approved                              | Yes  |
| CE Marked                                  | Yes  |
| Relative Humidity, Min                     | 50 %RH   |
| Relative Humidity, Max                     | 95 %RH   |
| IP Rating                                  | IP65<br>IP66   |
| Shock Acceleration (Max.)                  | 100 g  |
| Shock Duration (Max.)                      | 11 ms  |
| Vibration Acceleration (Max.)              | 10 m/s <sup>2</sup>  |
| Vibration Displacement (Peak to Peak Max.) | 1.52 mm  |
| Vibration Frequency, Operational (Max.)    | 2000 Hz  |
| Vibration Duration (Max.)                  | 180 min  |
| Standards Compliance                       | NEMA ICS-5<br>UL 508<br>EN 60947-1<br>EN 60947-5-1<br>EN 60947-5-5<br>EN 418                         |
| Certifications                             | UL<br>UR<br>CSA<br>CCC<br>CE   |
| Shipping Approvals                         | RINA (Registro Italiano Navale)<br>ABS (American Bureau of Shipping)<br>Lloyd's Register of Shipping |



## Catalogue No: **D7-AF1CE110**

## COLOUR CAP FOR FLUSH NON-ILLUM PUSHBUTTON WHITE DOWN





| REFERENCES                                  |                                  |
|---|----------------------------------|
| IECEx Certificate                           | -                                |
| Supplier Declaration of Conformity:         | -                                |
| Installation Guide:                         | -                                |
| User Manual:                                | -                                |
| Manufacturer Datasheet:                     | Series D7_Manufacturer Datasheet |
| Manufacturer Catalogue & Product Selection: | -                                |

