





UNO

UNO50W15WH

SAP CODE: 2001971



Photometric Diagram



Unit: cd
C0/180 110.0deg
C90/270 111.2deg

50W 1500mm White Linear LED batten

UNO is a linear LED batten with selectable color temperature with surface and suspension mount kits included.



TRITONE

Colour Changeable

KEY INFORMATION

Lumen Output	4150 / 4250 / 4200lm
Input Power	50W
Hole Cutout Size	N/A
Install	SUSPENDED / SURFACE MOUNT
Dimming Options	Non-Dimmable
Fitting Colour	WHITE
Warranty	5yr
IP Rating	IP40
IK Rating	N/A
IC Rating	N/A
Rebate Scheme Approvals	N/A

PHOTOMETRIC

Efficacy	83 / 85 / 84lm/W
LED	SMD
CCT	3000 / 4000 / 5000K
CRI	>80
Beam Angle	110°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	40V DC
Power Factor	>0.9
LED Input Current (nominal)	1300mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	1.2m Flex & Plug
Total Weight	2.2kg
Dimensions	1501 x 50 x 86.5mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1