Catalogue No: SBLWRF45LMMD

SIGNATURE BATTEN LED W/P NEXUS RF 4500Im MAINT W/MOT DET SEN

Stanilite Emergency and Exit Lighting > Signature > Monitored Signature > Signature Batten RF





Signature Batten LED Weather Proof Nexus RF 4500 lumens Maintained with Motion Detect Sensor

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- Hi-temp NiCad batteries.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Emergency Lighting	Batten
Testing System	Nexus RF Infinity
Operating Mode	Maintained
Operating Voltage	240 VAC
Power Consumption	49.0 W
Mounting	Surface - Universal
LED Life	75,000 hours
Lumen Output	4500 lumens
Integral Motion Sensor	yes
Battery Type	Ni-Cd
Height	90 mm
Width	140 mm
Depth	1260 mm
Base Colour	Grey
Diffuser Colour	Grey
Battery Replacement	03CBMA035P
IP Rating	IP65
IK Rating	IK08
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005



Catalogue No: SBLWRF45LMMD

SIGNATURE BATTEN LED W/P NEXUS RF 4500Im MAINT W/MOT DET SEN

Stanilite Emergency and Exit Lighting > Signature > Monitored Signature > Signature Batten RF

Stanline Emergency and Exit	Lighung > Signature > Monitored Signature > Signature Batteri KP	NHP
REFERENCES		
IECEx Certificate	-	
Supplier Declaration of Conformity:	Weatherproof LED Battens, NiCad or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)	
Installation Guide:	-	
User Manual:	-	
Manufacturer Datasheet:	-	
Manufacturer Catalogue & Product Selection:	-	

