



Representative Photo Only
(actual product may vary based on configuration selections)

HANDLE PANEL IP66 RED 100-125A

- Double break per pole offers high durability and short-circuit withstand
- Use of glass fibre reinforced polyester provides high mechanical and thermal resistance (does not include SLBM or VLBM modular series)
- Quick and easy to install thanks to good centre to centre distance and connection accessories including copper connecting links.
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage
- All Socomec load break switches are compatible with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), padlocking, UV and chemical agent resistive material and the choice of standard blue or red / yellow colour

SPECIFICATIONS

Component Type Power Distribution & Protection	Handle
Number of Poles	1
Ie, Rated Operational Current, AC-21a, 415V	125 A@415V
Details, Switch	SLBM 100...125A
Handle Type	Pistol type
Colour, Bezel	Yellow
Colour, Handle	Red & Yellow colour
Details, text	"OFF" padlockable, "ON" locking field convertible. Front and side operation. S0 type handle.
IP Rating	IP65
Padlockable	Yes

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	14841111_Manufacturer Product Selection Guide